

W101 & W201 AUTOMATIC ROTARY MACHINE

Fill with precision.
Seal with fortitude.
Deliver with integrity.



FEATURES

- Perimeter Guard with safety interlocks
- Touch screen HMI mounted on pack-off side
- Complete fault diagnostics
- Camco precision drive
- Safety sensors indicate no cup, no fill, & no foil

ADDITIONAL OPTIONAL COMPONENTS

- Hot fill adaptable
- Fill tube sizes allow a large range of cup volumes
- Feed options include hoppers (heated hopper available) and pipping systems
- Level Control System
- Date coding for the top, side, or bottom
- Manual or robotic pack off systems
- Pneumatically controlled positive shut off valves and cup lifts

OPERATIONAL REQUIREMENTS

- Single operator (excluding pack-off)
- 220v single phase on a 20-amp circuit
- 90 PSI Clean & dry compressed air

BENEFITS

- Entirely automatic system maintains mess & waste
- Very low maintenance
- Modular construction enables growth
- Compact footprint: Approximately 6' high & 4 sq. ft area
- W101 - up to 40 cups per minute
- W201 - up to 80 cups per minute

STATION OVERVIEW



1. Cup Load
2. Filler Zone 1
3. Filler Zone 2 (W201) Secondary Filler (W101)
4. Foil Placement
5. Heat Seal
6. Unload



WILPACK
PACKAGING

1665 ELMWOOD ROAD
ROCKFORD, IL 61101
815.490.9235

SALES@WILPACKPACKAGING.COM
WILPACKPACKAGING.COM

